# ROOFING SELECTION GUIDE

Luxury, Designer & Traditional Roofing Shingles







# You know it when you see it.

It's not just a roof.
It's a CertainTeed roof.

Quality. Durability. Style. Color.

When you select a roof for your home, there's a lot to consider.


That's when a roof becomes more than just a roof. The same way a home is more than just a house.

You want the best for your home and everything in it.

So why guess, when you can be Certain?







**COLOR AVAILABILITY** 

### **GRAND MANOR®**

- Two full-size, fiberglass-based shingles with randomly applied tabs
- Authentic depth and dimension of natural slate
- Virtual five-layer coverage when applied
- 425 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty – group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart™ protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- High-Performance Starter and hip and ridge accessory available (see details in back of brochure)
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

#### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

#### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5

### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.


### **Quality Standards:**

























### **BELMONT®**

- Authentic depth and dimension of natural slate
- 275 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty - group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart™ protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- High-Performance Starter and hip and ridge accessory available (see details in back of brochure)
- All colors are available in an Impact Resistant version



\* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

### Wind Resistance:


- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5

### Impact Resistance:

 All colors available in a version that meets UL2218 Class 4



### CARRIAGE HOUSE®

- Two full-size, fiberglass-based shingles
- Unique chamfered cut for scalloped appearance
- Four-layer coverage when applied
- 350 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty - group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart<sup>™</sup> protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- Hip and ridge accessory available (see details in back of brochure)

\* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- $\bullet$  UL certified to meet ASTM D3018 Type 1  $\,$

#### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

#### **Tear Resistance:**

- UL certified to meet ASTM D3462
- CSA standard A123.5

### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**

• ICC-ES-ESR-1389 & ESR-3537












### **GRAND MANOR and CARRIAGE HOUSE SHINGLES**


These two shingles can be combined to create a myriad of custom patterns, emulating traditional slate roof designs.














### PRESIDENTIAL SHAKE® TL

- Three-piece laminated fiberglass construction
- Distinctive sculpted, rustic look
- 475 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty – group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart™ protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- Presidential Starter (required) and hip and ridge accessory available (see details in back of brochure)
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F


#### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5

### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**



### PRESIDENTIAL SHAKE®

- Two-piece laminated fiberglass construction
- Distinctive sculpted, rustic look
- 355 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty
   group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart<sup>™</sup> protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- Presidential Starter (required) and hip and ridge accessory available (see details in back of brochure)
- \* See warranty for specific details and limitations.
- \*\* Color available in impact resistant version.
- \*\*\* ENERGY STAR qualified product called Presidential Solaris® Gold meets both solar reflectance and thermal emissivity requirements.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

#### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5

### Impact Resistance:

 Select colors (\*\*) available in version that meets UL2218 Class 4

### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

#### **Quality Standards:**















### **COLOR AVAILABILITY**











### LANDMARK® PREMIUM

- Two-piece laminated fiberglass-based construction
- Classic shades and dimensional appearance of natural wood or slate
- 300 lbs. per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty
   group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart™ protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- CertainTeed Starter and hip and ridge accessory available (see details in back of brochure)
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F


### **Tear Resistance:**

- UL certified to meet ASTM D3462
- CSA standard A123.5

### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**



### LANDMARK PRO®

- Two-piece laminated fiberglass-based construction
- Classic shades and dimensional appearance of natural wood or slate
- 250 lbs. per square
- Lifetime limited transferable warranty - residential\*
- 50-year limited transferable warranty - group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart<sup>™</sup> protection
- 15-year 110 mph wind-resistance warranty
- · Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- CertainTeed Starter and hip and ridge accessory available (see details in back of brochure)
- \* See warranty for specific details and limitations

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

#### Tear Resistance:

- UL certified to meet **ASTM D3462**
- CSA standard A123.5

### Wind Driven Rain Resistance:

• Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**











































- algae-resistance warranty
- 10-year SureStart™ protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- CertainTeed Starter and hip and ridge accessory available (see details in back of brochure)

### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5

### Wind Driven Rain Resistance:

• Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**

<sup>\*</sup> See warranty for specific details and limitations.



### LANDMARK®

### Impact Resistant

- Fiberglass-based construction
- 250 lbs. per square
- Lifetime limited transferable warranty\*
- 10-year SureStart™ protection
- 10-year StreakFighter® algae-resistance warranty
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- \* See warranty for specific details and limitations.



CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

• UL Class A

### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

### Tear Resistance:

- UL certified to meet ASTM D3462
- CSA standard A123.5-98

### **Impact Resistance:**

• UL2218 Class 4

### Wind Driven Rain Resistance:


 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.


### **Quality Standards:**


















### LANDMARK SOLARIS PLATINUM







### LANDMARK SOLARIS®

Solar Reflective Shingles

- Two-piece laminated fiberglass-based construction
- Classic shades and dimensional appearance of natural wood or slate
- 250 lbs. per square
- Meets ENERGY STAR requirements
- Lifetime limited transferable warranty residential\*
- 50-year limited transferable warranty group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart™ protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required

### Landmark Solaris Solar Reflectivity (SR), Thermal Emittance (TE) & Solar Reflectance Index (SRI) Data

	Color	CRRC Rated Product Directory							
Product		Solar Reflectance		Thermal Emittance		Solar Reflective Index		CA 2016 Title 24*	Energy Star Certified
		Initial	Aged	Initial	Aged	Initial	Aged	Ş₽	Sta
Landmark Solaris" Gold	Max Def Resawn Shake	0.26	0.25	0.88	0.90	26	25	YES	YES
Landmark Solaris" Gold	Max Def Weathered Wood	0.25	0.24	0.90	0.89	25	24	YES	YES
Landmark Solaris" Platinum	Coastal Tan	0.40	0.36	0.91	0.90	45	40	YES	YES
Landmark Solaris" Platinum	Santa Fe	0.40	0.35	0.90	0.91	45	39	YES	YES
Landmark Solaris" Platinum	Sierra Buff	0.41	0.37	0.92	0.90	47	41	YES	YES

<sup>\*</sup> Can be used to comply with the 2016 California Title 24 Part 6 Cool Roof Requirements.

<sup>\*</sup> See warranty for specific details and limitations.



### HIGHLAND SLATE®

- Single layer fiberglass-based construction
- Blended shades and dimensional appearance of natural slate
- 8" exposure, 18" x 36" size, 240 lbs per square
- Lifetime limited transferable warranty – residential\*
- 50-year limited transferable warranty – group-owned or commercial\*
- 15-year StreakFighter® algae-resistance warranty
- 10-year SureStart<sup>™</sup> protection
- 15-year 110 mph wind-resistance warranty
- Wind warranty upgrade to 130 mph available. CertainTeed starter and CertainTeed hip and ridge required
- Impact Resistant version available (Select colors\*\*)



\* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Certified to meet ASTM D3018, Type 1
- UL 790 Class A
- ASTM E 108 Class A

#### Wind Resistance:

- UL 2390/ASTM D 6381 Class H
- ASTM D3161 Class F

#### **Tear Resistance:**

- UL Certified to meet ASTM D3462
- CSA Standard A123.5

### Impact Resistance:

 Select colors (\*\*) available in version that meets UL2218 Class 4


### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**

























### PATRIOT Product only available in select areas.

- Architectural style shingles
- Single layer fiberglass-based construction
- Intricate color blend drops combined with intermittent shadow lines
- 215 lbs. per square
- 30-year limited transferable warranty\*
- 10-year StreakFighter® algae-resistance warranty
- 8-year SureStart<sup>™</sup> protection
- 10-year 110 mph wind-resistance warranty
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

#### Wind Resistance:

- UL certified to meet ASTM D3161
- UL certified to meet ASTM D7158 Class H

### **Tear Resistance:**

- UL certified to meet ASTM D3462
- CSA standard A123.5

### **Quality Standards:**

### TRADITIONAL SHINGLES



In addition to a full contingent of luxury and designer shingles (architectural shingles), CertainTeed features the industry's broadest line of traditional shingles (3-tab shingles). They're all designed for long-lasting performance and durability.

### CT<sup>™</sup> 20

- Fiberglass composition
- 195 lbs. per square
- 20-year limited transferable warranty\*
- 3-year SureStart™ protection
- 5-year 60 mph wind-resistance warranty
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

#### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

### Tear Resistance:

• UL certified to meet ASTM D3462

### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**

• ICC-ES-ESR-1389 & ESR-3537

Cedar Brown Dove Gray Moire Black Weathered Wood

### CERTAINTEED XT™25

- Fiberglass composition
- 205 lbs. per square
- 25-year limited transferable warranty\*
- 10-year StreakFighter® algae-resistance warranty
- 5-year SureStart<sup>™</sup> protection
- 5-year 60 mph wind-resistance warranty
- \* See warranty for specific details and limitations.

CertainTeed products are tested to ensure the highest quality and comply with the following industry standards:

#### Fire Resistance:

- UL Class A
- UL certified to meet ASTM D3018 Type 1

#### Wind Resistance:

- UL certified to meet ASTM D3018 Type 1
- ASTM D3161 Class F

### **Tear Resistance:**

UL certified to meet ASTM D3462

### Wind Driven Rain Resistance:

 Miami-Dade Product Control Acceptance: Please reference www.certainteed.com to determine approved products by manufacturing location.

### **Quality Standards:**

• ICC-ES-ESR-1389 & ESR-3537

Black Cedar Brown Cinnamon Frost Dove Gray Evergreen Blend Heather Blend Mint Frost Moire Black Nickel Gray Oakwood Silver Lining Slate Gray Star White Tile Red Blend Timber Blend Weathered Wood

### HIP AND RIDGE ACCESSORIES



### Shangle® Ridge Accessory

- Hip and ridge capping
- · Two full layers
- 12" width allows application over standard ridge vents
- Full 8" exposure
- Matches all Grand Manor, Highland Slate, Carriage House and Belmont colors
- · Algae resistant



### Solaris® Hip and Ridge

- Used for hip and ridge capping
- Matches Landmark Solaris shingle colors
- Covers 33.75 lineal feet per bundle; 24 shingles per bundle



### Shadow Ridge®

- Used for hip and ridge capping
- · Single-layer coverage for product versatility
- · Sealant strip for maximum adherence
- Dimensions are 12" x 12", with a 5" exposure
- Can be used on shingle-over vents or directly over centerline of hip or ridge
- Available in complementary product colors (see individual Roofing Plant Catalogs for color availability)



### Cedar Crest®

- Dimensions are (overall) 12" x 36", separated into individual pieces 12" x 12", with an 8" exposure
- · Covers 20 lineal feet per bundle
- Matches Landmark Series, Presidential Shake, Presidential Shake TL, Highland Slate and Belmont colors





# Integrity Roof System™

Integrity is built from the bottom up. Layer-on-layer, only CertainTeed provides the peace of mind that comes with the best components performing together for peak efficiency.



- Waterproof Underlayment
  - Waterproofing shingle underlayment prevents leaks from wind-driven rain and ice dams
- High-performance underlayment provides a water-resistant layer over the roof deck and a secondary barrier against leaks
- 3. Starter Shingles

  Perfect starts every time and designed to work in tandem with the roof shingles above

- 4 Roof Shingles
  Choose the best, covered by the strongest warranty in the business
- 5. Hip & Ridge Caps

  Perfect finish for hip and ridge lines, complementing all CertainTeed shingles
- Engineered for ideal roof ventilation especially when matched with CertainTeed Intake Vents

# StreakFighter® algae-resistance protection

StreakFighter is a special feature that protects a wide range of CertainTeed shingles from the streaking, spotting and discoloration caused by airborne algae. It helps safeguard a roof's beauty, especially in humid areas.

### SureStart™ protection

Because CertainTeed roofing products are manufactured to the highest quality standards, we confidently include the additional assurance of SureStart™ protection with all CertainTeed shingles. SureStart provides the strongest protection you can get in the vital early years after your new roof has been installed.

Simply put, if a manufacturing defect is discovered during the SureStart period, CertainTeed will provide reimbursement of 100% of the cost of the shingles and labor to repair the defective shingles



to repair the defective shingles or apply new shingles to replace the defective shingles. See actual warranty for details and limitations.

### Roofers' Select®

This revolutionary high-performance underlayment combines new technology with the best attributes of true 15 and 30 lb. felt.

- · Lays flat and is extremely resistant to wrinkling
- Reduces the likelihood of slipping for increased safety
- Doesn't tear away from fasteners when walked on or in strong wind



 Meets underlayment requirements for the CertainTeed Integrity Roof System™

### DiamondDeck®

DiamondDeck is a synthetic, scrim-reinforced, water-resistant underlayment that can be used beneath shingle, shake, metal, or slate roofing. It is manufactured to provide best-in-class performance in terms of both weather protection and contractor safety. 10-square roll (4-foot wide and 250-foot long) is easier to handle and faster to apply than standard felt rolls.



### WinterGuard®





When snow and ice melt, trapped water can infiltrate to damage the roof deck and building interior.

WinterGuard is installed under shingled roofing to prevent water damage from ice dams, as well as wind-driven rain.

WinterGuard is designed for use on roof decks as a waterproofing underlayment beneath shingle, slate and tile roofs to prevent leakage due to water backup from ice dams or wind-driven rain. WinterGuard HT, an advanced waterproofing underlayment, is specially formulated to resist high roof temperatures and is the only WinterGuard product to be warranted for use under metal roofs. WinterGuard is most commonly used in critical areas such as roof eaves, valleys and low-slope applications.

For specific details and limitations, refer to the actual product warranties.

### RoofRunner™

Lightweight synthetic polymer-based underlayment outperforms felt and outclasses other synthetics. Designed for use on roof decks as a water-resistant layer beneath asphalt roofing shingles, this scrim-reinforced underlayment includes a special top surface treatment that provides excellent slip resistance, even when wet. Large roll size - 4ft wide x 250 ft long - speeds application.

# MetaLayment® Self-Adhering Metal Underlayment

MetaLayment has a tough, tear-resistant film on its top surface that will not scratch roofing metal applied over it. The adhesive bottom surface of MetaLayment is protected with a disposable silicone-coated release film, which is split longitudinally down the middle for easier application. Manufactured to meet ASTM D1970.

# Color Companion Products<sup>™</sup> for Flat Roof Areas

With CertainTeed Flintlastic® SA, you can coordinate flat roof areas like carports, canopies and porches with your main roof. Flintlastic SA is a self-adhering low slope roofing product available in eight colors that complement some of the most popular CertainTeed shingles.

### SELECTION GUIDE

LUXURY SHII	NGLES	Shingle Construction and Description	Weight (lbs. per square)	UL Class A Fire Resistance Rating	UL Certified to Meet ASTM D3462	UL Certified to Meet ASTM D3018 Type 1	UL 2218 Impact Resistance Rating	ASTM D3161 Wind Resistance	
Grand Manor		Two full-size, fiberglass-based shingles with randomly applied tabs; Authentic depth and dimension of natural slate; Virtual five-layer coverage when applied	425	>	>	<b>&gt;</b>		Class F, 110 mph	
Belmont Impact Resistant Version Available		Single layer, fiberglass-based shingles with randomly applied tabs; Authentic depth and dimension of natural slate	275	~	~	V	Class 4	Class F, 110 mph	
Carriage House	uu	Two full-size, fiberglass-based shingles; Unique chamfered cut for scalloped appearance; Four-layer coverage when applied	350	>	>	V		Class F, 110 mph	
Presidential Shake TL	Service of the servic	Three-piece laminated fiberglass construction; Distinctive sculpted, rustic look	475	<	<	~		Class F, 110 mph	
Presidential Shake  Impact Resistant Version Available (Select colors)	THE	Two-piece laminated fiberglass-based construction; Distinctive sculpted, rustic look	355	<b>&gt;</b>	>	V	Class 4	Class F, 110 mph	
Presidential Solaris Gold	trent!	Two-piece laminated fiberglass-based construction; Distinctive sculpted, rustic look	355	~	~	V		Class F, 110 mph	
DESIGNER SHINGLES									
Landmark Premium	0700	Two-piece laminated fiberglass-based construction; Classic shades and dimensional appearance of natural wood or slate	300	>	>	V		Class F, 110 mph	
Landmark Pro	0700	Two-piece laminated fiberglass-based construction; Classic shades and dimensional appearance of natural wood or slate	250	~	~	~		Class F, 110 mph	
Landmark Impact Resistant Version Available	0000	Two-piece laminated fiberglass-based construction; Classic shades and dimensional appearance of natural wood or slate	229/235 250	~	>	٧	Class 4	Class F, 110 mph	
Landmark Solaris	0700	Two-piece laminated fiberglass-based construction; Classic shades and dimensional appearance of natural wood or slate	250	~	~	V		Class F, 110 mph	
Highland Slate  Impact Resistant Version Available (Select colors)		Single layer fiberglass-based construction; Blended shades and dimensional appearance of natural slate	240	<b>&gt;</b>	>	٧	Class 4	Class F, 110 mph	
Patriot	707.833	Architectural style shingle; Single layer fiberglass-based construction; Intricate color blend drops combined with intermittent shadow lines	215	~	~	V		Class F, 110 mph	
TRADITIONAL SHINGLES									
XT 25		Fiberglass composition; Designed for long-lasting performance and durability	205	~	~	V		Class F, 110 mph	
CT 20		Fiberglass composition; Designed for long-lasting performance and durability	195	~	~	~		Class F, 110 mph	

<sup>\*\*</sup> Wind warranty upgrade to 130 mph available.

Miami-Dade Product Control Acceptance	Conforms To CSA Standard A123.5	Limited Transferable Warranty Against Manufacturing Defecton Residential Applications '50-Year on Group-owned or Commercial Applications	StreakFighter algae-resistance Warranty (where availab)	SureStart Protection	Wind-Resistance Warranty Upgraded wind warranty available. See warranty for details and limitations	Shingle Size	Bundles Per Square			
~	V	Lifetime*	15-year	10-year	15-year 110 mph **	18" x 36" 8" Exposure	5			
	<b>V</b>	Lifetime*	15-year	10-year	15-year 110 mph **	18" x 36" 8" Exposure	4			
٧	>	Lifetime*	15-year	10-year	15-year 110 mph **	18" x 36" 8" Exposure	5			
>	~	Lifetime*	15-year	10-year	15-year 110 mph **	14 1/4" x 40" 4" Exposure	6			
>	>	Lifetime*	15-year	10-year	15-year 110 mph **	14 1/4" x 40" 4" Exposure	5			
٧	<b>&gt;</b>	Lifetime*	15-year	10-year	15-year 110 mph **	14 1/4" x 40" 4" Exposure	5			
~	>	Lifetime*	15-year	10-year	15-year 110 mph **	13 1/4" x 38 3/4" 5 5/8" Exposure	4			
~	~	Lifetime*	15-year	10-year	15-year 110 mph **	13 1/4" x 38 3/4" 5 5/8" Exposure	3			
~	V	Lifetime	10-year	10-year	15-year 110 mph **	13 1/4" x 38 3/4" 5 5/8" Exposure	3			
٧	>	Lifetime*	15-year	10-year	15-year 110 mph **	13 1/4" x 38 3/4" 5 5/8" Exposure	3			
>	~	Lifetime*	15-year	10-year	15-year 110 mph **	18" x 36" 8" Exposure	3			
	~	30-year	10-year	8-year	10-year 110 mph	13 1/4" x 39 3/8" 5 5/8" Exposure	3			
~		25-year	10-year	5-year	5-year 60 mph	12" x 36" 5" Exposure	3			
~		20-year		3-year	5-year 60 mph	12" x 36" 5" Exposure	3			
CertainTeed starter and CertainTeed hip and ridge required. *** With approved underlaymen										

(9)(6)

\*\*\* With approved underlayment

### **High-Performance Starter**

Starter Course shingle specifically for use with Grand Manor, Belmont and Highland Slate—and the only approved installation alternative to using the shingles themselves.

- 10" x 36", 102 lineal ft. per bundle, 34 shingles per bundle
- Provides labor and cost savings by not cutting shingles
- Dual sealant strip for increased wind resistance
- Better look with straight factory-cut eave edge

### **Presidential Starter**

Required for Presidential Shake TL and Presidential Shake applications.

- 13 1/4" x 40" (required double layer), 36.5 lineal ft. per bundle (based on 2-layer application), 22 shingles per bundle
- Two layers of straight factory-cut eave edge
- Available in the entire Presidential Shake TL and Presidential Shake color line
- · Assures Class A fire rating
- Saves significant installation time

### CertainTeed Swiftstart®

CertainTeed Swiftstart metric starter shingle is designed specifically for use with CertainTeed Landmark Series shingles. Rather than cutting expensive field shingles to use as starters, you can save time and money by starting with Swiftstart.

- Code-compliant, meets min. 2" headlap requirement for metric shingles; many competing products do not
- Each 18-piece bundle covers 116 lineal ft.
- Recommended for use to obtain enhanced warranties

### Ventilation

- CertainTeed Ridge Vent 12" unfiltered
- CertainTeed Ridge Vent 12" filtered
- CertainTeed Rolled Ridge Vent unfiltered
- CertainTeed Intake Vent filtered
- CertainTeed Static Vent Aluminum and Plastic






# What's behind our #1 rating?

Builders and remodelers across America know certain things to be true of CertainTeed. For starters, we've been in the roofing business for over 100 years. We have thousands of satisfied homeowners. The process of building that satisfaction begins the moment you turn to us.

CertainTeed offers you the broadest range of color and style choices. But you'll see it's not style over substance. You'll get a roof that's made from the highest quality materials and backed by a strong warranty program. It's our promise to you: quality made certain, satisfaction guaranteed.

# MATTERHORN®

Metal Roofing



Because it's more than just a roof

**Matterhorn Metal Roofing** takes the form of slate, tile or wood shake to create a beautiful roof that makes a lasting impression.

Replicate the charm of artisanal roofing at a fraction of the cost with durable, lightweight steel.

Includes a lifetime limited warranty. Laboratory tested to resist fire, wind and hail.

Features a proprietary multi-coat paint system that offers 17 hyper-realistic color options across all profiles, including 14 CRRC-rated cool roofing colors.



## RESIDENTIAL ROOFING



learn more at: certainteed.com/roofing



### **CertainTeed Corporation**

ROOFING • SIDING • TRIM • DECKING • RAILING • FENCE • GYPSUM • CEILINGS • INSULATION

20 Moores Road Malvern, PA 19355 Professional: 800-233-8990 Consumer: 800-782-8777 certainteed.com